

**SINGLE LADDER FOR LOW-VOLTAGE LIVE WORKING**  
COMPLIANT WITH **EN 50-528** | **<1000 V /1500 V**



## THE + HELIOS

- High-visibility composite profiles
- Lightweight and high-strength design with closed round edge rectangular profiles
- Unique patented screw rung/stile connection enables rungs and stiles to be replaced
- Non-slip ribbed rubber ladder feet
- D-shaped aluminium rungs, spaced at 250 mm Ultragrip® technology deeply serrated
- Ø 100 mm wall wheels

## SPECIAL FEATURES

- Optional :
  - Clam cleats and rope kit for securing the ladder before climbing
  - Rubber cushioned V-shaped pole leaning device
  - Stabiliser/leveller adjustable up to 18cm for uneven surfaces. Opens with one-foot operation



  
MADE IN FRANCE


Find all our products on [www.audinnov.fr](http://www.audinnov.fr)

AUDINNOV - 3 ZA du Pasquier - 71800 Varennes-sous-Dun  
Tél. : +33 (0) 3 85 28 01 41 - [contact@audinnov.fr](mailto:contact@audinnov.fr)


**audinnov**<sup>®</sup>  
SAFETY FIRST

*Because we care!*

**SINGLE LADDER FOR LOW-VOLTAGE LIVE WORKING**  
 COMPLIANT WITH **EN 50-528 | <1000 V /1500 V**



Optional : clam cleats and rope Ø 10.5



D-shaped rungs



Ribbed rubber ladder feet



Optional : Stabiliser/leveller

Non-contractual information V EN 07.3- AUDINNOV

Product code	Length	Weight	Number of rungs
SINGLE SECTION LADDER			
101139	1,5 m	5 kg	5
101138	1,75 m	6 kg	6
101130	2.0 m	7 kg	7
101131	2.5 m	8 kg	9
101132	3,0 m	9 kg	11
101133	3.5 m	10 kg	13
101134	4,0 m	12 kg	15
101135	5,0 m	14 kg	21
101136	6,0 m	15 kg	23