



### Product features

- High-visibility orange-coloured composite profiles
- Lightweight and high-strength design with closed round edge rectangular profiles
- Unique patented screw rung/stile connection enables rungs and stiles to be replaced
- Non-slip ribbed rubber ladder feet
- D-shaped aluminium rungs, spaced at 250 mm «Ultra-grip» technology deeply striated
- Ø 100 mm wall wheels



### Various optional accessories available

- Clam cleats and rope kit for securing the ladder before climbing
- Rubber cushioned V-shaped pole grip
- Integrated ladder safety stabiliser/leveller adjustable up to 18cm for uneven surfaces. Opens with one-foot operation

# HELIOS

**SINGLE NON-CONDUCTIVE LADDER FOR LOW-VOLTAGE LIVE WORKING**

**EN 50-528 V2010 COMPLIANT**



MADE IN FRANCE




**LOW- VOLTAGE LIVE WORKING <1000V A.C/1500AV D.C**

POLE GRIP AND WALL WHEELS



OPTIONAL CLAM CLEATS AND Ø 10.5 ROPE



D-SHAPED RUNG

« ULTRA-GRIP » RIBBED RUBBER LADDER FEET



STABILISER / LEVELLER



Model
-------

Length	Weight	Number of rungs
--------	--------	-----------------

00101131
00101132
00101133

SINGLE LADDER		
2.5 m	12 kg	9
3 m	15 kg	11
3.5 m	17 kg	13